

HygroMATIK
 MORE THAN
40 YEARS
 HUMIDIFICATION

HeaterCompact KIT

Our heater type steam humidifier HeaterCompact is now also available as an installation kit. The HeaterCompact KIT offers hygienic steam, free from minerals, and comes in seven unit sizes with maximum steam capacities from 2 kg/h to 27 kg/h. From climate chambers over bakery ovens to clean room workbenches, well-known manufacturers rely on the established quality of our heater type steam humidifier installation kits. High quality, ready to fit components and thought-through technology warrant easy fitting and a long service life. If you purchase larger numbers, it can be manufactured according to your requirements regarding voltage and design of your panel.



All signals are set to green

- Hygienic humidification with mineral-free steam
Steam output from 2 to 27 kg/h
- For all water qualities up to 15° German hardness
- Re-usable steam cylinder
- Nearly maintenance-free when operated with fully demineralised water
- Fast steam production
- Sturdy blow-down pump
- Simple maintenance, no special tools required
- Highest operational safety by double safety concept
- Servicefriendly: Steam hose adapter and O-ring set are included

Optional:

- Continuous or 1-step control
- SuperFlush rinsing system

Type		HC02 KIT	HC03 KIT	HC06 KIT	HC06 KIT	HC09 KIT	HC12 KIT	HC18 KIT	HC27 KIT
Steam output	[kg/h]	2	3	6	6	9	12	18	27
Electrical supply *		230V/1/N				400V/3/N			
Electrical power	[kW]	1,5	2,25	4,5	4,5	6,8	9	13,5	20,3
Current	[A]	6,6	9,8	19,6	11,3	16,9	19,5	29,3	29,3
Fuse	[A]	1x10	1x10	1x20	3x16	3x20	3x25	3x35	3x35
Control (optional)		Basic, Comfort, ComfortPlus							
Control voltage	[V]	230							
Number of heating elements		1				2		3	
Steam hose connection	[mm]	1x25	1x40 (reducing piece to DN25 available)						
Condensate hose connection	[mm]	1x12							
Empty weight	[kg]	3,5	10	10	10	10	13	13	14
Operational weight	[kg]	5	13	13	13	13	31	31	32
Outer dimensions	Height [mm]	308		428			571		
Height from steam outlet	Width [mm]	321		321			346		
	Depth [mm]	221		221			289		
Water supply		Fully demineralised water/cleaned condensate/ partially softened or standard tap water, 1 to 10 bar, for connection 3/4"							

* other voltages on request
 Subject to technical changes

HygroMATIK

Airtrend Ltd.-Gobrid. Ltd.

Kumanovska 14, 11000 Beograd Tel. +381 11 383 68 86, 308 57 40 Faks +381 11 344 41 13
 E-mail: gobrid@eunet.rs