CTVK Supply air diffusedstavništvo u Beogradu


Kumanovska 14, 11000 Beograd


Tel: 011/3836886, 3085740

Faks: 011/3444113 e-mail: gobrid@eunet.rs web: www.airtrend.rs



# **CTVK Supply air diffuser**







The CTVK is a very quiet supply air diffuser designed for wall mounting. The diffuser is suitable for use in small premises, such as offices, houses and hotel rooms. The air discharged from the valve is mixed thoroughly with the room air thus providing a draught-free air supply. The air flow is adjustable.

The design of the CTVK minimizes the risk of dust deposits forming on the wall surface. The valve is easy to install and easy to keep clean since it has large, smooth surfaces.

#### **Quick Selection**

fully open slot

Diffuser	Air flow range I/s at sound level					
	25 dB	30 dB	35 dB			
CTVK-100	14	-	-			

- = outside working area

## Specifications


- Adjustable flow
- Easy to install
- Easy to clean

Product code example Supply air diffuser CTVK-100 Mounting ring KGEZ-01-100




## **Selection diagrams**

## Throw, zone length



## Air flow



## Sound power level

Correction of sound level in dB at								
CTVK	octave bands, middle frequency, Hz							
	63	125	250	500	1000	2000	4000	8000
100	2	-3	-3	0	0	-3	-6	-10

Sound power levels by octave bands are obtained by adding to total sound pressure level  $L_{p10A}$ , dB(A) the corrections  $K_{oct}$  presented in the table according to the following formula:

$$L_{Woct} = L_{p1OA} + K_{oct}$$

Correction  $K_{\text{oct}}$  is average value in range of use of CTVK unit

Note! In installations where CTVK is mounted together with KGEZ-43 angle duct, the sound power level will increase by 3 dB(A).



## **Sound attenuation**

Sound attenuation in dB at								
CTVK	octave bands, middle frequency, Hz							
	63	125	250	500	1000	2000	4000	8000
100	24	20	18	12	10	10	10	10

The average sound attenuation  $\Delta L$  from duct to room including the end reflection of the connecting duct in wall installation, is obtained in the table above.

# Air stream diffusion

 $b_v = 0.1 \times l_{0.2}$ 


 $b_h = 0.6 \times l_{0.2}$ 

where  $l_{0,2}$  = 1,2 x zone length




# **Dimensions and weights**

# Supply air valve CTVK-100




Weight: 0.4 kg

Mounting ring KGEZ-01-100, fit-in connection/ Mounting ring KGEZ-05-100, fit-on connection



Weight: 0.1 kg


## Angle duct KGEZ-43



Size	Α	В	С	D1	D2	Weight
Size	[mm]	[mm]	[mm]	[mm]	[mm]	[kg]
100 - 080	120	39	148	125	79.3	0.4
100 - 100	140	39	98	125	99.3	0.4

# Mounting frame KGEZ-12-100







2670 GB 2018.02.23

Weight: 0.2 kg


## Installation

Supply air valve connected to a mounting ring






# Supply air valve connected to an angle duct




## Supply air valve connected to a mounting frame





## Adjustment



#### General

## Application and function

The CTVK is a very quiet supply air diffuser designed for wall mounting. The diffuser is suitable for use in small premises, such as offices, houses and hotel rooms.

The air discharged from the diffuser is mixed thoroughly with the room air thus providing a draught free air supply. The air flow is adjustable.

The design of the CTVK minimizes the risk of dust deposits forming on the wall surface. The diffuser is easy to install and easy to keep clean since it has large, smooth

#### Material and surface finish

Air diffuser CTVK is made of hot-dip galvanized steel sheet.

The diffusers are powder coated for a high surface finish and good impact and scratch resistance. Standard colour white RAL 9010. Other colours on request.

#### Instructions

Directions for installation, adjustment and care are set out in detail in our technical instruction which accompanies each product. The instruction is also accessible on www.flaktgroup.com.

#### Technical data and dimensioning

For complete dimensioning details, please see FläktGroup product selection program. Contact our nearest sales office for further information.

#### Packaging

The air diffuser is supplied as standard in a cardboard box containing 20 pieces. Weight: 8 kg, volume: 0,04 m<sup>3</sup>

#### Descriptive text

Supply air diffuser CTVK manufactured by FläktGroup, with mounting ring or angle duct.



Product code

Size (aaa)

100

Supply air valve Supply air valve, special colour CTVK-aaa CTVK-aaa-E Accessories and spare parts

Accessories

Mounting ring - insertion KGEZ-01-bbb

connection

Mounting ring - fit-on connection KGEZ-05-bbb

Size (bbb) 100

Angle duct for CTVK-100 KGEZ-43-bbb-ccc

Size (bbb-ccc) Connection diameter in mm to valve – to duct: 100–080, 100–100

Spare parts

Seal COGZ-100-6

Spring COSZ-100-1