

Technical Data Centrifugal Atomiser DG

Type	DG4	DG 8
Humidification capacity [kg/h]	4	8
Effective volume ** [m ³]	400	1200
Circulation air [m ³ /h]	350	600
Motor power rate [kW]	0,14	0,16
Electrical supply *	230V/ 50 Hz/1N	400 V/50 Hz/3N
Nominal current [A]	0,65	0,58
Diameter [mm]	450	620
Height [mm]	280	390
Water supply		
Feed [bar]	1-6	1-10
	R 1/4"	R 1/4"
Safety overflow	R 1/2"	R 1/2"
Empty weight [kg]	4,5	15
Operational weight [kg]	5	15,5

* Other voltages on request.

** Varies depending on room temperature and required room humidity.

Subject to technical amendments without notice.

Our Service for you

- HygroMatik distributors in more than 35 countries worldwide
- Manuals, planing tools and workshop offers are available online at www.airtrend.rs



HYGROMATIK
WE HUMIDIFY THE AIR

AIRTREND Limited

Predstavništvo u Beogradu
Kumanovska 14, 11000 Beograd
Tel: 011 383 68 86, 308 57 40
Faks: 011 344 41 13
e-mail: gobrid@eunet.rs
web: www.airtrend.rs